



A standard docket provides you with useful productivity data, such as:

- 1 Date and time
- 2 Company name
- 3 Loader operator identification
- 4 Loader identification
- 5 Truck identification
- 6 Docket identification
- 7 Customer name
- 8 Product loaded and total truck load weight
- 9 Individual bucket load weights
- 10 Weight units (lb, ton, kg)

More detailed reports can also be produced depending on the console model, such as:

- Shift, daily or weekly accumulated totals
- Product identification
- Daily product totals such as:
 - Daily customer totals – summary of total product loaded for customer (customer report)
 - Daily truck totals – summary of total product loaded for trucks (truck report)

The Loadrite Printer is suitable for single or duplicate paper.

Loadrite Printer: The Nuts and Bolts

Note: Specifications may change due to continuous product improvement.

Power Requirements

Supply Voltage 11.2 to 32VDC. Automotive power supply transient suppression exceeds relevant SAE specifications
Supply Current (when printing) 0.4A typical, 2 max @ 24VDC 0.75A typical, 3.0A max @ 12VDC
Stand-by Current 50mA

Physical

Dimensions W120 x L240 x D135mm including bracket
Case Injection moulded polycarbonate alloy
Keypad Rugged membrane keyboard
Indicator Lamps LED type. Online. Out of paper and Ready
Buttons On front panel – On/Off Line, Paper Feed, Test Print Functionality

Environmental

Operating Temperature -10°C to 50°C
Humidity 20 to 90% relative humidity
Protection Water and dust protected to IP32
Method Dot matrix impact on plain paper. Inking by autofeed, replaceable ribbon cassette

Printing

Paper Plain calculator paper, 57mm wide up to 57mm roll diameter
 Optional 2 layer NCR paper for duplicate copy
Print Format 24 character columns, 5 x 8 dot matrix characters, 1.7 x 2.7mm
Test Print All alphanumeric ASCII characters are printed
Print Speed 1.7 lines/sec typical. Paper feed 4 lines/sec typical



Call your local distributor today to discuss how the Loadrite Printer will meet your specific requirements

- Full on-site operator training
- National and international network of factory-trained distributors
- Loadrite products are used in over 30 countries
- 25 years industry experience

Australia

Call free: 1 800 655 860
 Phone: 02 9542 7810
 Fax: 02 9542 7820

New Zealand

Phone: 07 575 2209
 Fax: 07 575 2251

Email: info@loadritescales.com
www.loadritescales.com



The manufacturer of Loadrite holds ISO 9001:2000 quality management systems certification.

LOADRITE