

LOADRITE SPRINT

It's so cost effective, it'll pay for itself...



Install the Loadrite Sprint on your forklift or small wheel loader and see how you'll save time and money. This cost-effective onboard weighing system combines basic functions required to load once and load right, along with Loadrite's exceptional service and support. With only six keys the Loadrite Sprint is operator friendly and simple to use.

Install a Loadrite Sprint and reduce costs by:

- Loading accurately the first time
- Eliminating costly overload fines
- Minimising lost product from overloading
- Reducing wear and tear on machines caused by overloading stresses

The Loadrite Sprint is ideal for small wheel loaders working on construction sites and forklifts situated in warehouses.

LOADRITE

The Ultimate in Onboard Weighing Systems

The Loadrite Sprint's features include:

- Large LCD display with back lighting for night and low light operation
- Time/date display
- Only six keys – so it's operator friendly and easy-to-use
- Basic weighing functions
- Seven language options including English, Spanish and French
- Long total function – shows total product moved over a shift, week or month
- Auto add function – the Sprint automatically adds the lifted weight to the weighing total
- Total function – shows the total weight of a product loaded onto a truck
- Load information such as summary reports can be produced with the Loadrite Printer or transferred to the Loadrite Material Management System (both sold separately)

Loadrite Sprint Console: The Nuts and Bolts

Note: Specifications may change due to continuous product improvement.

Power Requirements	Supply Voltage 12 to 32 VDC (i.e. designed to operate on 12 or 24 volt systems). Automotive power supply transient suppression exceeds SAE specifications Supply Current 160 mA typical, 350 mA max, 3A max with printer Calibration and Data Back Up Data is stored in a permanent memory and is not affected when the main power is turned off
Display/Keyboard	Display LCD 2 lines of 8 characters, used to display operator messages, and prompts to enter product data etc The large, highly visible, backlit 5 digit numeric display shows lifted weights and totals Keyboard Waterproof tactile membrane with backlighting
Physical	Dimensions W145 x L240 x D110 mm Weight 1.5 kg
Environmental	Operating Temperature -10°C to 50°C Storage Temperature -30°C to 80°C Protection Water and dust protected to IP54 Vibration Qualified to MIL-STD-810D

Accessories: Loadrite Printer, Loadrite Material Management System

Call your local distributor today to discuss a solution that meets your specific requirements...



- Full on-site operator training
- National and international network of factory-trained distributors
- Loadrite products are used in over 30 countries
- 25 years industry experience

Australia

Call free: 1 800 655 860
Phone: 02 9542 7810
Fax: 02 9542 7820

New Zealand

Phone: 07 575 2209
Fax: 07 575 2251

Email: info@loadritescales.com
www.loadritescales.com



The manufacturer of Loadrite holds ISO 9001:2000 quality management systems certification.

LOADRITE